

# All products made-to-order


# Ceiling Panel | Fabric

Finish Durability

Conwed Panels are reliable, all-purpose acoustic solutions. Capable of multiple levels of durability, highly-customizable finishes, and mounting options, this product is suitable for schools, auditoriums, theaters, offices, and libraries: anywhere noise control is needed.

**Respond Series** 

# Items to specify







Click for full specsheet conwed.com/specsheet-ceilingpanel-fabric-hi

# Mounting type



Rotofast

Snap-on

Anchors







### Hotmelt fabric adhesion

Provides superior bond strength lasting the lifetime of the product. Easily reactivated for field repairs and modification.

### Corners



Square

# Fabric partners

Carnegie kvadrat Guilford of Maine **DesignTex** maharam

# Edge profile



Square

### Fire rating

Conwed products meet or exceed ASTM F84 standards for smoke development and flame spread on a component level.



### **Shapes**



### Washable

Refer to the Maintenance & Cleaning Guide for more details.

conwed.com/cexpmaintenanceandcleaning



## Sustainability

For your LEED projects, our products can help you qualify for different points depending on the product you choose. Contact us to learn more detailed information.

To view our certificate visit conwed.com/cexp-LEED.



### Warranty

3 years. Refer to Warranty for more details

conwed.com/cexpwarranty

# Max size availabilities

- Standard core max size
- NAF (No-Added-Formaldehyde core) max size

Thickness	36"×96"
] 1/16"	• 0
2 1/16"	• 0
3 1/16"	• 0

Minimum size of 12"x12"

# **Acoustic performance**

The NRC of the products are determined from an average of sound absorption coefficients, obtained from tests conducted according to ASTM C423 procedures in an NVLAP accredited laboratory.

HZ →	125	250	500	1000	2000	4000	NRC ↓
1 1/16"	0.13	0.45	0.93	1.07	1.06	1.00	0.90
2 1/16"	0.26	0.87	1.09	1.03	1.01	1.05	1.00
3 1/16"	0.32	0.95	1.09	1.06	1.03	1.00	1.05