

# **SelectSound by Owens Corning**

This product is engineered for high acoustic performance while being incredibly discrete. Fill large spaces or gaps between beams with this matte black, anti-reflecting fiberglass composite. Perfect for theaters, performance centers, and stadiums.

# **Board vs. Blanket**

SelectSound Blankets fill spaces similar to insulation. It can be covered with other decorative and perforated materials to be used as an acoustic backer or filler. SelectSound Boards are meant for more visible areas, smoothly filling in spaces and gaps with a flat matte

#### Core construction

Black fiberglass composite core for high acoustic performance. Boards finished with a smooth matte black layer.

# **Board**



2. Black matte finish



1. Black fiberglass core

## **Acoustic performance**

The NRC of the products are determined from an average of sound absorption coefficients, obtained from tests conducted according to ASTM C423 procedures in an NVLAP accredited laboratory.

|         | HZ →         | 125  | 250  | 500  | 1000 | 2000 | 4000 | NRC ↓ |
|---------|--------------|------|------|------|------|------|------|-------|
| Blanket | 1" thickness | 0.05 | 0.03 | 0.60 | 0.87 | 0.98 | 1.05 | 0.70  |
| Bla     | 2" thickness | 0.12 | 0.66 | 1.04 | 1.08 | 1.04 | 1.07 | 0.95  |
| Board   | 1" thickness | 0.06 | 0.25 | 0.62 | 0.91 | 0.99 | 0.98 | 0.70  |
| Bo      | 2" thickness | 0.18 | 0.71 | 1.12 | 1.12 | 1.03 | 1.02 | 1.00  |

### Size availabilities

Only sold in whole packs.

|         | Thickness | 72"x70' | 48"x50' | 48"x96" |
|---------|-----------|---------|---------|---------|
| Blanket | ן"        | •       |         |         |
| Blar    | 2"        | •       | •       |         |
| Board   | 7"        |         |         | •       |
| Box     | 2"        |         |         | •       |



Square





| Edge details               | Mounting | Finish             |
|----------------------------|----------|--------------------|
| Available choices include: | _        | Black matte finish |



#### Fire Rating

Conwed products meet or exceed ASTM E84 standards for smoke development and flame spread on a component level.



#### **Quick Installation**

This product is easy to install on drywall or concrete surfaces using impaling clips and adhesive.



**Shapes** 





#### Washable

Refer to the Maintenance & Cleaning Guide for more details.

conwed.com/cexpmaintenanceandcleaning

# **Sustainability initiatives**



For your LEED projects, our products can help you qualify for different points depending on the product you choose. Contact us to learn more detailed information. To view our certificate visit **conwed.com/cexp-LEED**.

## Warranty

3 years. Refer to Warranty for more details. conwed.com/cexp-warranty

