




## Diffusers: Barrel & Pyramidal

**Barrel & Pyramidal Diffusers** are designed to scatter and blend sounds, rather than absorb, to improve the sound experience of spaces. Pyramidals affect all frequencies they come in contact with, while Barrels only scatter low and high frequencies.

### Product features



#### Core construction:

Constructed of 1/8" thermoformed, fire-resistant plastic and molded to a one-piece barrel or a special offset pyramidal shape. The interior can be lined with a 1 1/2" thick layer of fiberglass batt to enhance sound absorption.

Size availability	Edge details	Finishes	Mounting	Shapes
<ul style="list-style-type: none"> <li>Pyramidal: 2'x2', 2'x4', 4'x4'</li> <li>Barrel: 2'x2', 2'x4', 3'x3', 4'x2', 4'x3', 4'x4', 4'x8'*, 6'x3'*, 6'x4'*, 8'x4'*</li> </ul> <p><i>*These sizes are available in rigid fiberglass only. Custom shapes and sizes are available upon request.</i></p>	Edge details shall be flanged for laying into grid or straight for wall and some ceiling applications.	<ul style="list-style-type: none"> <li>White with lemon peel texture (unfinished gelcoat)</li> <li>White with haircell texture (unfinished thermoformed)</li> <li>Fabric coverings</li> <li>Chosen paint color application</li> <li>Smooth gel coat</li> </ul>	<ul style="list-style-type: none"> <li>Mount using a combination of L-angles and hook and loop fasteners.</li> <li>Ceiling diffusers come in flanged configuration to fit standard ceiling grid. 1 1/2" wide.</li> </ul>	—

Custom size is our standard.

### Acoustic performance

The NRC of the products are determined from an average of sound absorption coefficients, obtained from tests conducted according to ASTM C423 procedures in an NVLAP accredited laboratory.

	HZ →	125	250	500	1000	2000	4000	NRC ↓
Barrel (Gel-D5)		0.29	0.29	0.08	0.05	0.06	0.05	0.10
Barrel (Gel-E400)		0.30	0.23	0.09	0.08	0.06	0.08	0.10
Barrel (Therm-D5)		0.34	0.14	0.08	0.06	0.06	0.05	0.10
Barrel (Therm-E400)		0.25	0.11	0.10	0.06	0.06	0.06	0.10
Pyramidal (Therm-D5)		0.19	0.14	0.10	0.08	0.06	0.03	0.10
Pyramidal (Therm-E400)		0.31	0.11	0.09	0.08	0.07	0.09	0.10

### Additional properties

\*Conwed products meet or exceed ASTM E84 standards for smoke development and flame spread on a component level.

	Fire rating*	Impact resistant	Scratch resistance	NAF available	Washable	Warranty
Barrel	1/A (ASTM E84)	—	—	—	✓	3 years (from date of shipment received)
Pyramidal	1/A (ASTM E84)	—	—	—	✓	

### Initiatives

#### Sustainability

Conwed is committed to driving sustainability wherever possible. By streamlining our processes and using recycled materials in our products, we strive to decrease our environmental impact. Our materials are certified by leading social responsibility groups and are helping us pave the way toward a more sustainable future.



For your LEED® projects, our products can help you qualify for different points depending on the product you choose. Contact us to learn more detailed information.

Disclaimer of liability: Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Conditions of use may vary and are beyond our control, and because of this Conwed makes no representation about, and is not responsible or liable for, the accuracy or reliability of data associated with particular uses of any product described herein.