




## New Dimensions Baffles: Solid Core

**New Dimensions** Baffles are designed for areas requiring excellent sound absorption with a custom painted finish. With the entire Sherwin-Williams catalog at your disposal, and custom color matching available to you, New Dimensions can meet even your most challenging design requirements. Use in conference rooms, auditoriums, churches, entryways, etc.

### Product features



#### Core construction:

Dimensionally-stable 6-7 PCF fiberglass board, covered with a specially-formulated fiberglass scrim, and finished with paint. The acoustically transparent finish completely covers the face and exposed edges. Edges are protected with a resin hardening.

| Size availability   | Edge details   | Finishes  | Mounting   | Shapes |
|---|--|---|--|--------|
| <ul style="list-style-type: none"> <li>Thicknesses: 1 1/2", 2"</li> <li>Standard max: 4'x10'</li> </ul> | All edges are resin hardened, unless otherwise specified.<br><br>Available choices include: <ul style="list-style-type: none"> <li>Square</li> </ul> | Custom paint. Please reference Sherwin-Williams catalog at <a href="http://sherwin-williams.com">sherwin-williams.com</a> .<br><br>Color matching available. All color matching requires customer to approve sample(s) before fulfilling order. | Standard mountings: <ul style="list-style-type: none"> <li>Acoustical spring anchor</li> </ul> | —      |

**Custom size is our standard.**

### Acoustic performance

The values are standard sabins per baffle panel mounted in accordance with ASTM C 423 (Type J Mounting) 2", 24 x 48 baffle.

| HZ →             | 125  | 250  | 500   | 1000  | 2000  | 4000  | SABINS ↓           |
|------------------|------|------|-------|-------|-------|-------|--------------------|
| 1 1/2" thickness | —    | —    | —     | —     | —     | —     | —                  |
| 2" thickness     | 1.62 | 5.14 | 11.13 | 16.71 | 16.43 | 15.46 | <b>1.54 per sf</b> |

### Additional properties

\*Conwed products meet or exceed ASTM E84 standards for smoke development and flame spread on a component level.

|                  | Fire rating*   | Impact resistant | Scratch resistance | NAF available | Washable | Warranty                         |
|------------------|----------------|------------------|--------------------|---------------|----------|----------------------------------|
| 1 1/2" thickness | 1/A (ASTM E84) | —                | —                  | ✓             | —        | 3 years                          |
| 2" thickness     | 1/A (ASTM E84) | —                | —                  | ✓             | —        | (from date of shipment received) |

### Initiatives

#### Sustainability

Conwed is committed to driving sustainability wherever possible. By streamlining our processes and using recycled materials in our products, we strive to decrease our environmental impact. Our materials are certified by leading social responsibility groups and are helping us pave the way toward a more sustainable future.



For your LEED® projects, our products can help you qualify for different points depending on the product you choose. Contact us to learn more detailed information.

Disclaimer of liability: Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Conditions of use may vary and are beyond our control, and because of this Conwed makes no representation about, and is not responsible or liable for, the accuracy or reliability of data associated with particular uses of any product described herein.