




Respond® A Baffles: Back-to-Back

Respond® A Baffles are economical, all-purpose acoustic panels designed for use where sound absorption and value are the main criteria. A vast variety of fabric finish options, from the leading fabric suppliers, offer you great design customization. This product is suitable for schools, auditoriums, theaters, offices, and libraries: anywhere sound control is needed and critical lighting and high abuse resistance are not factors.

Product history: Respond® A Baffles: Fold-Up have been discontinued. This change occurred on 06/22/2020.

Product features



Core construction:

Dimensionally-stable 6-7 PCF fiberglass board, covered with custom fabric completely adhered to the face of the panel. Fabric is returned to the back of each piece for a visible seam across all sides. All corners are fully tailored. Edges are protected with resin hardening.

Size availability	Edge details	Finishes	Mounting	Shapes
<ul style="list-style-type: none"> Overall thicknesses: 2", 3", 4" Standard max: 4'x10' <p>Custom size is our standard.</p>	<p>All edges are resin hardened, unless otherwise specified.</p> <p>Available choices include:</p> <ul style="list-style-type: none"> Square Half Bevel 	<p>A wide variety of fabrics are available from all major brands, including:</p> <ul style="list-style-type: none"> Carnegie Maharam Designtex Knoll Guilford of Maine 	<p>Standard mountings:</p> <ul style="list-style-type: none"> D-Rings 	<p>—</p>

Acoustic performance

The sabins of the products are determined from an average of sound absorption coefficients, obtained from tests conducted according to ASTM C423 procedures in an NVLAP accredited laboratory.

	HZ →	125	250	500	1000	2000	4000	SABINS ↓
2" overall thickness		—	—	—	—	—	—	—
3" overall thickness		—	—	—	—	—	—	—
4" overall thickness		—	—	—	—	—	—	—

Additional properties

*Conwed products meet or exceed ASTM E84 standards for smoke development and flame spread on a component level.

	Fire rating*	Impact resistant	Scratch resistance	NAF available	Washable	Warranty
2" overall thickness	1/A (ASTM E84)	—	—	✓	✓	3 years (from date of shipment received)
3" overall thickness	1/A (ASTM E84)	—	—	—	✓	
4" overall thickness	1/A (ASTM E84)	—	—	✓	✓	

Initiatives

Sustainability

Conwed is committed to driving sustainability wherever possible. By streamlining our processes and using recycled materials in our products, we strive to decrease our environmental impact. Our materials are certified by leading social responsibility groups and are helping us pave the way toward a more sustainable future.



For your LEED® projects, our products can help you qualify for different points depending on the product you choose. Contact us to learn more detailed information.

Disclaimer of liability: Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Conditions of use may vary and are beyond our control, and because of this Conwed makes no representation about, and is not responsible or liable for, the accuracy or reliability of data associated with particular uses of any product described herein.