



Tile

Conwed Tiles bring the best acoustic performance out of traditional drop-grid ceilings, whether they're in the original spec, or a retrofit. Schools, offices, and more can all benefit.

Print


Acoustic Art

Any of Conwed's main products can be custom-printed for a truly unique look, making *Acoustic Art*. Print image guidelines can be found at Conwed.com/CEXP-printrequirements

Core construction

Dimensionally-stable 6-7 PCF fiberglass board for acoustic performance. Surface is completely adhered with specially-formulated scrim, and finished with custom-printed imaging. Layer of 1/8" impact-resistant (IR) material for added durability and tackability. Edges hardened for durability using resin and finished with solid black paint for decorative purposes.

1. Resin hardened edge
2. Fiberglass core
3. IR layer
4. Print Finish



Acoustic performance

The NRC of the products are determined from an average of sound absorption coefficients, obtained from tests conducted according to ASTM C423 procedures in an NVLAP accredited laboratory.

HZ →	125	250	500	1000	2000	4000	NRC ↓
1 1/8" thickness	0.09	0.48	0.93	1.13	1.10	1.03	0.90
2 1/8" thickness	—	—	—	—	—	—	—

Max size availabilities

Thickness	2'x8'
1 1/8"	✓
2 1/8"	✓

NAF Core Thicknesses also available in No-Added-Formaldehyde cores are indicated with **red checkmarks**.

Larger images can be spread over multiple panels

Copyright disclaimer: Users acknowledge that all images, names, dates, and other content added to their design are correct and they own all copyrights to them or have full authorization to use them.

Edge details	Mounting	Finish
All edges are resin hardened with a black painted finish. Available choices include: • Lay-in: Square	Fits in standard ceiling grid systems Grid sizes: Standard 1 5/16" Designer 9/16"	Images can be applied to individual products, or spread over many to form massive mosaics. Contact Customer Service for more info on how we can support your complex projects.



Fire Rating

Conwed products meet or exceed ASTM E84 standards for smoke development and flame spread on a component level.



Impact Resistant

This product has an impact-resistant layer for protection in high-traffic areas.



Shapes

—



Cleanable

Refer to the Maintenance & Cleaning Guide for more details.
conwed.com/cexp-maintenanceandcleaning



Warranty

3 years. Refer to Warranty for more details.
conwed.com/cexp-warranty

Sustainability initiatives



LEED®

For your LEED projects, our products can help you qualify for different points depending on the product you choose. Contact us to learn more detailed information. To view our certificate visit conwed.com/cexp-LEED.