




## Access Ceiling

Access gets its name from its easy-to-use downward-hinged access panels. This uniform system completely hides the suspension, maintains proper panel alignment, and allows a custom paint finish. Access shines in large spaces where access to mechanical equipment, network trays, and electrical is needed on a regular basis.

### Core construction

Dimensionally-stable 6-7 PCF fiberglass board with a 1/8" 16-20 PCF molded glass facer. All system components are rust-free aluminum and galvanized steel to minimize maintenance

1. Aluminum grid frame
2. Fiberglass core
3. Panel finish



### Acoustic performance

The NRC of the products are determined from an average of sound absorption coefficients, obtained from tests conducted according to ASTM C423 procedures in an NVLAP accredited laboratory.

HZ →	125	250	500	1000	2000	4000	NRC ↓
1 1/8" thickness	0.09	0.48	0.93	1.13	1.10	1.03	0.90

### Max size availabilities

Custom size is our standard

Thickness	4'x10'	
1 1/8"	•	◦

**NAF Core** No-Added-Formaldehyde core max size indicated with red dot.



#### Edge details

- Slight bevel



#### Mounting

- Standard mountings: Torsion spring mounting, extruded aluminum grid mains and V-shaped spacer bars.



#### Finishes

- Fabric coverings
- Custom paint color



#### Fire Rating

Conwed products meet or exceed ASTM E84 standards for smoke development and flame spread on a component level.



#### Standard Durability

This product has a durable core construction, ideal for out-of-reach areas.



#### Shapes

—



#### Connecting

—



#### Washable

Refer to the Maintenance & Cleaning Guide for more details.  
[conwed.com/cexp-maintenanceandcleaning](http://conwed.com/cexp-maintenanceandcleaning)

### Sustainability initiatives



For your LEED projects, our products can help you qualify for different points depending on the product you choose. Contact us to learn more detailed information. To view our certificate visit [conwed.com/cexp-LEED](http://conwed.com/cexp-LEED).

### Warranty

3 years. Refer to Warranty for more details.  
[conwed.com/cexp-warranty](http://conwed.com/cexp-warranty)



Disclaimer of liability: Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Conditions of use may vary and are beyond our control, and because of this Conwed makes no representation about, and is not responsible or liable for, the accuracy or reliability of data associated with particular uses of any product described herein.