



Tile

Conwed Tiles bring the best acoustic performance out of traditional drop-grid ceilings, whether they're in the original spec, or a retrofit. Schools, offices, and more can all benefit.


Fabric | A ▶ Respond A

Conwed's fabric-wrapped products, known as the *Respond Series*, are made with the leading textile manufacturers. **Fabric | A products don't rely on any additional layers of material for our standard durability.**

Core construction

Dimensionally-stable 6-7 PCF fiberglass board for acoustic performance. Surface is completely adhered with a custom fabric, wrapping around for fully-finished edges. Edges hardened for durability using resin.

1. Resin-hardened edge
2. Fiberglass core
3. Fabric Finish



Acoustic performance

The NRC of the products are determined from an average of sound absorption coefficients, obtained from tests conducted according to ASTM C423 procedures in an NVLAP accredited laboratory.

HZ →	125	250	500	1000	2000	4000	NRC* ↓
1" thickness	0.04	0.28	0.73	1.07	1.11	1.13	0.80
1 ½" thickness	0.10	0.53	1.06	1.15	1.09	1.06	0.95
2" thickness	0.11	0.79	1.16	1.15	1.09	1.12	1.05

*These NRC values are from direct-attach tests of the same product. NRC values for this application are equal to or greater than these values.

Max size availabilities

Thickness	2'x8'	
1"	•	◦
1 ½"	•	
2"	•	◦

NAF Core No-Added-Formaldehyde core max sizes indicated red dot.



Edge details	Mounting	Finish
<p>All edges are resin hardened, unless otherwise specified.</p> <p>Available choices include:</p> <ul style="list-style-type: none"> • Lay-in: Square • Tegular: ¾", 1½" • Gridlock: 1½" 	<p>Fits in standard ceiling grid systems</p> <p>Grid sizes: Standard 1½" Designer ¾"</p>	<p>A wide variety of fabrics are available from all major brands, including:</p> <p>Carnegie DESIGNTEX maharam Knoll Guilford of Maine kvadrat</p>



Fire Rating

Conwed products meet or exceed ASTM E84 standards for smoke development and flame spread on a component level.



Standard Durability

This product has a durable core construction, ideal for out-of-reach areas.



Shapes

—



Connecting

—



Washable

Refer to the Maintenance & Cleaning Guide for more details.
conwed.com/cexp-maintenanceandcleaning

Sustainability initiatives



For your LEED projects, our products can help you qualify for different points depending on the product you choose. Contact us to learn more detailed information. To view our certificate visit conwed.com/cexp-LEED.

Warranty

3 years. Refer to Warranty for more details.
conwed.com/cexp-warranty



Disclaimer of liability: Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Conditions of use may vary and are beyond our control, and because of this Conwed makes no representation about, and is not responsible or liable for, the accuracy or reliability of data associated with particular uses of any product described herein.

Click for latest document version
conwed.com/datasheet-tile-fabric-a