



All products made-to-order

Baffle | Print | IR

Product

Finish

Durability

► Acoustic Art

Conwed Baffles bring the performance you expect from a world-class acoustic solution to the growing trend of baffles. Combined with the Conwed Express Hanging System, any space can be perfectly fitted with highly customizable baffles.

Items to specify

- Preinstalled connection points
- Painted resin-hardened edge
- Fiberglass core
- IR layer
- Scrim
- Printed image

Finish wrapped on all sides

Durability level ▶

A IR HI

Mounting type

Preinstalled connection points ready for suspension hardware

Conwed Express Hanging System is an optional add-on

Corners

Square

Edge profile

Square

Edges are painted with a black painted finish.

Custom Print Finish

File requirements
 Vector: AI, EPS, SVG, PDF
 Raster: JPG, TIFF, PDF, PSD
 Resolution: 300 DPI
 Max file size: 1 GB

[Click for full specsheet](https://conwed.com/specsheet-baffle-print)
conwed.com/specsheet-baffle-print

[Click for full print requirements](https://conwed.com/cexp-printrequirements/)
conwed.com/cexp-printrequirements/

Fire rating

Conwed products meet or exceed ASTM E84 standards for smoke development and flame spread on a component level.

Shapes

This product can be made into custom shapes for complex designs. Contact Customer Service for more info on how we can support your project.

Washable

Refer to the Maintenance & Cleaning Guide for more details.
conwed.com/cexp-maintenanceandcleaning

Sustainability

For your LEED projects, our products can help you qualify for different points depending on the product you choose. Contact us to learn more detailed information.
To view our certificate visit conwed.com/cexp-LEED.

Warranty

3 years. Refer to Warranty for more details.
conwed.com/cexp-warranty

Max size availabilities

- **Standard core** max size
- **NAF (No-Added-Formaldehyde core)** max size

Thickness	4'x8'
2 1/4"	• ○

Acoustic performance

The NRC of the products are determined from an average of sound absorption coefficients, obtained from tests conducted according to ASTM C423 procedures in an NVLAP accredited laboratory.

HZ →	125	250	500	1000	2000	4000	NRC ↓
2 1/4"	0.09	0.48	0.93	1.13	1.10	1.03	0.90

*These NRC values are from direct-attach tests of the same product. NRC values for this application are equal to or greater than these values.

Minimum size of 12"x12"

Larger images can be spread over multiple panels

Copyright disclaimer: Users acknowledge that all images, names, dates, and other content added to their design are correct and they own all copyrights to them or have full authorization to use them.



Disclaimer of liability: Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Conditions of use may vary and are beyond our control, and because of this Conwed makes no representation about, and is not responsible or liable for, the accuracy or reliability of data associated with particular uses of any product described herein.

[Click for latest document version](https://conwed.com/datasheet-baffle-print)
conwed.com/datasheet-baffle-print