

Wall Panel

Product

Fabric

Finish


A

Durability

Conwed Panels are reliable, all-purpose acoustic solutions. Capable of multiple levels of durability, highly-customizable finishes, and mounting options, this product is suitable for schools, auditoriums, theaters, offices, and libraries: anywhere noise control is needed.


► Respond Series

Items to specify



[Click for full specsheet](https://conwed.com/specsheet-wallpanel-fabric-a)
conwed.com/specsheet-wallpanel-fabric-a

Mounting type



Hotmelt fabric adhesion

Provides superior bond strength lasting the lifetime of the product. Easily reactivated for field repairs and modification.

Corners



Edge profile



* Connect products with kerf & spline

Fabric partners

Carnegie kvadrat Guilford of Maine
DESIGNTEX Knoll maharam



Fire rating

Conwed products meet or exceed ASTM E84 standards for smoke development and flame spread on a component level.



Shapes

This product can be made into custom shapes for complex designs. Contact Customer Service for more info on how we can support your project.



Washable

Refer to the Maintenance & Cleaning Guide for more details.
conwed.com/cexp-maintenanceandcleaning



Sustainability

For your LEED projects, our products can help you qualify for different points depending on the product you choose. Contact us to learn more detailed information.
To view our certificate visit conwed.com/cexp-LEED.



Warranty

3 years. Refer to Warranty for more details.
conwed.com/cexp-warranty

Max size availabilities

- Standard core max size
- NAF (No-Added-Formaldehyde core) max size

Thickness	4'x10'	4'x12'	5'x10'	24 sqft
1/2"	•			
3/4"	•			
1"	◦	•	•	
1 1/2"	•			
2"	◦	•	•	
3"	◦	•	•	
4"				• ◦

Acoustic performance

The NRC of the products are determined from an average of sound absorption coefficients, obtained from tests conducted according to ASTM C423 procedures in an NVLAP accredited laboratory.

HZ →	125	250	500	1000	2000	4000	NRC ↓
1/2"	0.27	0.25	0.31	0.77	0.93	0.79	0.50
3/4"	-0.01	0.19	0.54	0.95	1.07	1.04	0.70
1"	0.04	0.28	0.73	1.07	1.11	1.13	0.80
1 1/2"	0.10	0.53	1.06	1.15	1.09	1.06	0.95
2"	0.11	0.79	1.16	1.15	1.09	1.12	1.05
3"	0.13	1.09	1.20	1.12	1.08	1.07	1.10
4"	0.14	1.07	1.18	1.11	1.07	1.08	1.10



Disclaimer of liability: Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Conditions of use may vary and are beyond our control, and because of this Conwed makes no representation about, and is not responsible or liable for, the accuracy or reliability of data associated with particular uses of any product described herein.