



All products made-to-order

# Wall Panel

Product

# Mineral

Core

# A


Durability

Conwed Panels are reliable, all-purpose acoustic solutions. Capable of multiple levels of durability, highly-customizable finishes, and mounting options, this product is suitable for schools, auditoriums, theaters, offices, and libraries: anywhere noise control is needed.

► TK/AC

Tackable surface

## Items to specify



Mineral core  
Fabric finish

### Mounting type



Z-clip to dw bracket



Impaling clips/adhesive



Z-Clip plate to DW Bracket or Z-bar

### Hotmelt fabric adhesion

Provides superior bond strength lasting the lifetime of the product. Easily reactivated for field repairs and modification.

### Corners

■  
Square

### Fabric partners

Carnegie **kvadrat** Guilford of Maine  
**DESIGNTEX** **Knoll** **maharam**

### Edge profile

■  
Square



Finish wrapped on all sides

### Durability level ▶

▼ ▼ ▼  
**A** IR HI

[Click for full specsheet](https://conwed.com/specsheet-wallpanel-mineral)  
[conwed.com/specsheet-wallpanel-mineral](https://conwed.com/specsheet-wallpanel-mineral)



### Fire rating

Conwed products meet or exceed ASTM E84 standards for smoke development and flame spread on a component level.



### Shapes

—



### Washable

Refer to the Maintenance & Cleaning Guide for more details.  
[conwed.com/cexp-maintenanceandcleaning](https://conwed.com/cexp-maintenanceandcleaning)



### Sustainability

For your LEED projects, our products can help you qualify for different points depending on the product you choose. Contact us to learn more detailed information.  
To view our certificate visit [conwed.com/cexp-LEED](https://conwed.com/cexp-LEED).



### Warranty

3 years. Refer to Warranty for more details.  
[conwed.com/cexp-warranty](https://conwed.com/cexp-warranty)

## Max size availabilities

- **Standard core** max size
- **NAF (No-Added-Formaldehyde core)** max size

Thickness	4'x4'
1/2"	•
5/8"	•

## Acoustic performance

The NRC of the products are determined from an average of sound absorption coefficients, obtained from tests conducted according to ASTM C423 procedures in an NVLAP accredited laboratory.

HZ →	125	250	500	1000	2000	4000	NRC ↓
1/2" thickness	—	—	—	—	—	—	—
5/8" thickness	0.09	0.23	0.32	0.37	0.47	0.54	<b>0.35</b>



Disclaimer of liability: Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Conditions of use may vary and are beyond our control, and because of this Conwed makes no representation about, and is not responsible or liable for, the accuracy or reliability of data associated with particular uses of any product described herein.

[Click for latest document version](https://conwed.com/datasheet-wallpanel-mineral)  
[conwed.com/datasheet-wallpanel-mineral](https://conwed.com/datasheet-wallpanel-mineral)